



CHILLER MODEL: GD-1.5H

230 Volt 1 Phase	
FLA	17
MCA	20
MOC	30

230 Volt 3 Phase	
FLA	15
MCA	17
MOC	25

460 Volt 3 Phase	
FLA	-
MCA	-
MOC	-

Dimensions ¹	30"W x 30"L x 30"H
Frame	Powder Coated Steel
Housing	Powder Coated Aluminum
Tank	12 Gallon Stainless Steel
Compressor HP	1.5
Condenser	Air-Cooled
Glycol Pump HP	0.5
GPM @ 25 PSI	20
Connection Size	1" FPT
Heat Exchanger	Stainless Steel Brazed Plate
Controls	Single Stage Digital

Electrical Enclosure	NEMA 4
Shipping Weight	450 lbs
Decibels @ 10'	60
Refrigerant	R404a

Cooling Capacity by Leaving Fluid Temperature²

LFT	Btu/H	kW
20 °F	8,460	2.5
30 °F	10,200	3.0
40 °F	12,400	3.6

¹Dimensions accurate for package chiller, remote condenser options will vary

²All capacities at 90 °F ambient

Chiller package consists of the following:

- Complete refrigeration circuit with scroll compressor
- Air-cooled condenser
- Glycol pump
- Fluid bypass valve
- All insulated copper piping
- Powder coated steel frame
- Powder coated aluminum housing
- Engineered high efficiency heat exchanger for maximum energy savings
- Digital temperature controller
- Insulated stainless steel glycol reservoir
- ETL (UL508) listed complete control panel with single point electrical connection, breakers, starters & safety switches
- Louvered aluminum access panels for easy service & maintenance
- Factory run tested and fully charged with refrigerant

1 Year Parts and Labor Warranty

