

CHILLER MODEL: GD-7x7H

230 Volt 1 Phase		
FLA	-	
MCA	-	
MOC	-	

230 Volt 3 Phase		
FLA	68	
MCA	75	
мос	102	

460 Volt 3 Phase		
FLA	32	
MCA	36	
мос	47	

Dimensions ¹	48"W x 89"L x 66"H	
Frame	Powder Coated Steel	
Housing	Powder Coated Aluminum	
Tank	115 Gallon Stainless Steel	
Compressor	7 HP (x2)	
Condenser	Air-Cooled	
Glycol Pump	2 HP	
Process Flow	65 GPM @ 25 PSI	
Connection Size	1.5" FPT	
Heat Exchanger	Stainless Steel Brazed Plate	
Controls	Microprocessor w/ Comm.	

Electrical Enclosure	NEMA 3R	
Ship/Operating Weight	1850/2450 lbs	
Decibels @ 10'	65 dBA	
Refrigerant	R448A	

Cooling Capacity by Leaving Fluid Temperature²

LFT	Btu/H	kW
20 °F	83,400	24.4
30 °F	103,400	30.3
40 °F	125,800	36.9

1. Package chiller dimensions, remote condenser options will vary


- 2. All capacities at 90 °F ambient
- 3. VFD available upon request


4. Specifications subject to change without notice

Chiller package consists of the following:


- Two complete refrigeration circuits
- Air-cooled microchannel condenser
- Glycol pump³
- Fluid bypass valve
- Freeze stat safety switch
- All insulated copper piping
- Powder coated steel frame
- Powder coated aluminum housing

- Engineered high efficiency heat exchanger for maximum energy savings
- Microprocessor controller with communication capabilities
- ETL (UL508) listed complete control panel with single point electrical connection, breakers, starters & safety switches
- Insulated stainless steel glycol reservoir
- Brass ball valves for supply and return glycol connections
- Louvered aluminum access panels for easy service & maintenance
- Factory run tested and fully charged with refrigerant





D



STATIONARY CHILLER • EST 1 993 • 760 BAILEY HILL ROAD EUGENE, OR 97402 • TEL (541) 345-3903 (800) 555-0973