

## FIRE & ICE MODEL: CH-3/10.5

| 230 Volt 1 Phase |   |  |
|------------------|---|--|
| FLA              | - |  |
| MCA              | - |  |
| MOC              | - |  |

| 230 Volt 3 Phase |    |
|------------------|----|
| FLA              | 28 |
| MCA              | 30 |
| MOC              | 35 |

| 460 Volt 3 Phase |    |  |
|------------------|----|--|
| FLA              | 15 |  |
| MCA              | 19 |  |
| MOC              | 20 |  |

| Dimensions      | 32"W x 52"L x 45"H              |
|-----------------|---------------------------------|
| Frame           | Powder Coated Steel             |
| Housing         | Stainless Steel                 |
| Tank            | 30 Gallon Stainless Steel       |
| Compressor      | 3 НР                            |
| Condenser       | Air-Cooled                      |
| Glycol Pump     | 0.75 HP                         |
| Process Flow    | 25 GPM @ 25 PSI                 |
| Connection Size | 0.75" Brass Quick Connects (x4) |
| Heat Exchanger  | Stainless Steel Brazed Plate    |
| Controls        | Single Stage Digital            |

| Heating Element               | 10.5 kW      |
|-------------------------------|--------------|
| Electrical Enclosure          | NEMA 3R      |
| Ship/Operating Weight         | 750/1000 lbs |
| Decibels @ 10'                | 62 dBA       |
| Refrigerant                   | R448A        |
| Cooling Capacity <sup>1</sup> | 21,800 Btu/h |
| Heating Capacity              | 35,800 Btu/h |

1. Capacity with 30 °F glycol LFT in 90 °F ambient

2. Specifications subject to change without notice

## Fire & Ice package consists of the following:

- Complete refrigeration circuit
- Air-cooled condenser
- Glycol pump
- Fluid bypass valve
- Freeze stat safety switch
- Digital temperature controller
- All insulated copper piping
- Stainless steel housing
- Powder coated steel frame
- Insulated stainless steel glycol reservoir

- Low watt density heating element specifically designed for glycol
- Engineered high efficiency heat exchanger for maximum energy savings
- Heavy duty rubber-on-steel casters for easy portability
- Brass quick connects for temperature control of up to 4 tanks at once without loss of glycol
- Complete set of 20 ft. glycol hoses and 25 ft. power cord
- ETL (UL508) listed complete control panel with single point electrical connection, breakers, starters & safety switches
- Louvered stainless steel access panels for easy service & maintenance
- Factory run tested and fully charged with refrigerant

