

CHILLER MODEL: GD-50H-1C-EM

230 Volt 1 Phase		
FLA	-	
MCA	-	
МОС	-	

230 Volt 3 Phase		
FLA 215		
MCA	263	
МОС	455	

460 Volt 3 Phase		
FLA	107	
MCA	131	
МОС	227	

Dimensions ¹	46"W x 167"L x 108"H	
Frame	Powder Coated Steel	
Housing	Powder Coated Aluminum	
Tank	N/A	
Compressor	50 HP	
Condenser	Vertical Discharge Air-Cooled	
Glycol Pump	2 HP	
Glycol Connection Size	2" Female NPT	
Heat Exchanger	Stainless Steel Brazed Plate	
Controls	Multi Stage Digital	

Electrical Enclosure	cal Enclosure NEMA 3R	
Shipping Weight	5100 lbs	
Decibels @ 10'	77 dBA	
Refrigerant	R448A	

Cooling Capacity by Leaving Fluid Temperature ²

LFT	Btu/H	kW
20 °F	315,000	92.3
30 °F	387,000	113.4
40 °F	468,000	137.2

- 1. Package chiller dimensions, remote condenser options will vary
- 2. All capacities at 90 °F ambient
- 3. Specifications subject to change without notice

Expansion module chiller package consists of the following:

- Complete refrigeration circuit
- Air-cooled condenser
- Chiller pump
- Freeze stat safety switch
- All insulated copper piping
- Female NPT glycol connections
- Powder coated steel frame
- Powder coated aluminum housing

- Semi-hermetic reciprocating compressor with capacity unloading
- Engineered high efficiency heat exchanger for maximum energy savings
- Digital temperature controller pre-wired for integration into expanding system
- ETL (UL508) listed complete control panel with single point electrical connection breakers, starters & safety switches
- Louvered aluminum access panels for easy service & maintenance
- Factory run tested and fully charged with refrigerant

